em wave inc.

Product Data Sheet



Fiberglass Base Station Antennas
EM-BFG11405-NJ (450-470 MHz)

- Broad Band Performance
- High Input Power Handling
- All Brass/Silver Plated Feed and Radiator Structure
- High Strength Filament Wound Fiberglass Radome (White)
- Exceeds 200mph (322kph) Wind Survival Rating
- DC Grounded for Static Dissipation and enhanced Lightning Protection

Electrical Specifications

Frequency Band	450-470 MHz
VSWR	<1.5:1
Impedance	50Ω
Gain / HPBW	5 dBi / 35º nominal
Power Rating	150 Watts
Polarization	Vertical, Linear
Radiation Pattern	Omni Directional
Lightning/Static Protection	DC Grounded

Mechanical Specifications

Dimensions	46 x 1.6 in. (1.17m x 40.5mm) [LxD]
EFPA	0.283 ft^2 (0.026m^2)
Wind Rating / Survival	200mph (322kph) / 224mph (360kph)
Connector	Type N, Jack
Radome	Fiberglass, Filament Wound, White
Connector Material, Finish	Brass, Silver
Mounting Kit	Sold Separately
Weight (Antenna), max	2 lb (0.9 kg)
Operational/Storage Temperature	-40°C to 85°C
Humidity	95% Condensing

Specifications subject to change without notification.

ELECTRO-MAGWAVE, INC.
2241 Pinnacle Parkway, Suite A, Twinsburg, OH 44087 t 216-453-1160 f 216-447-8828 www.emwaveinc.com