Product Data Sheet





EM-M11001-FME-058
EM-M11001-FME-195

NMO ¾" Hole Mount Cable Assembly

- RG-58/U or LL195 w/FME Connector attached
- Low-Profile
- Easy installation: Designed for a one-operator installation from above surface
- All brass components with silver plated contact.
- Heavy Duty mounting claw for reliable contact and ground connections

Radio Termination Adapters

(Sold Separately)



EMFME-TP FME to TNC Plug



EMFME-NP FME to N Plug



EMFME-MP FME to Mini-UHF Plug



EMFME-PL FME to PL259 Plug



EMFME-QP FME to QMA Plug

Electrical Specifications

Impedance	50Ω

Mechanical Specifications

Mounting Height	0.375 in. (9.5 mm)
Mounting Hole	0.75 in. (19.05 mm)
Mounting Application / Type	Thru-hole
Cable	RG-58/U or Low Loss195
Cable Length	17 ft. (5.1 m)
Connector Type	FME Attached
Material	Brass
Operating Temperature Range	-40° to 85° C
Mounting Surface Ingress Seal	O-Ring
Corrosion	Salt Fog
Humidity	95%

Specifications subject to change without notification.

ELECTRO-MAGWAVE, INC.
2241 Pinnacle Parkway, Suite A, Twinsburg, OH 44087 t 216-453-1160 f 216-447-8828 www.emwaveinc.com