Product Data Sheet



EM-MTR11001-FME-058
EM-MTR11001-FME-195

Thick Panel Series
NMO ¾” Hole Mount Cable Assembly

- RG-58/U or LL195 w/FME Connector Attached
- Precision 50Ω impedance
- Low Profile, self-adjusting NMO Locking Nut eliminates installation guesswork and time
- All brass & stainless steel components for maximum reliability & corrosion resistance
- Non-Rotational heady-duty centering washer. for precise hole alignment & non-slip, secure clamping pressure

Radio Termination Adapters

(Sold Separately)



EMFME-TP FME to TNC Plug



EMFME-NP FME to N Plug



EMFME-MP FME to Mini-UHF Plug



EMFME-PL FME to PL259 Plug



EMFME-QP FME to QMA Plug

Electrical Specifications

Impedance	50Ω

Mechanical Specifications

Mounting Hole	0.75 in. (19.05mm)
Mounting Application	Thick Panel, up to ½”, Thru-hole
Cable	RG-58/U or Low Loss 195
Cable Length	17 ft. (5.1m)
Connector Type	FME Attached
Material	Brass (Nickel), Stainless Steel
Operating Temperature	-40° to 85° C
Corrosion	Salt Fog
Humidity	95%
Mounting Surface Ingress Seal	O-Ring

Specifications subject to change without notification

ELECTRO-MAGWAVE, INC.
2241 Pinnacle Parkway, Suite A, Twinsburg, OH 44087 t 216-453-1160 f 216-447-8828 www.emwaveinc.com