em wave inc.

Product Data Sheet



e/m-Flex® EMFLX-M10001

Poly Spring VHF/UHF 2dBi Roof Mount Antenna

108-520 MHz

- NMO Mount, Black Chrome Finish
- Flexible Black Polymer Alloy Spring
- Broad Band, Field Tunable
- O-ring seal for waterproof construction
- Durable ASA base with TPU over mold dust seal and grip ring

Electrical Specifications

Frequency Band	(Tunable Range)	108-520 MHz
VSWR	(15 MHz Bandwidth @150 MHz)	<2.0:1
	(50 MHz Bandwidth @450 MHz)	<1.5:1
	(100 MHz @450 MHz)	<2.0:1
Impedance		50Ω
Gain		2 dBi
Power Rating		150 W
Polarization		Linear, Vertical
E-Plane		50 Degrees, Nominal
H-Plane		Omnidirectional
Ground-plane		Required

Mechanical Specifications

Overall Length	(@108 MHz)	29 in. (737mm)
	(@150 MHz)	19.75 in. (502mm)
	(@450 MHz)	7.75 in. (197mm)
Whip Material, Finish		17-7 SS, Black Chrome
Spring Material		Black Molded Polymer Alloy
Base Material		ASA w/TPU over mold grip ring
Mounting Application		¾ inch Thru-Hole NMO Mount
NMO Cable Assembly & Connector		Sold Separately
Operating Temperature		-40° to 85° C
Humidity		95%

Specifications subject to change without notification.

ELECTRO-MAGWAVE, INC.
2241 Pinnacle Parkway, Suite A, Twinsburg, OH 44087 t 216-453-1160 f 216-447-8828 www.emwaveinc.com