Product Data Sheet



e/m-FLEX® EMFLX-M10003-GPI

2 dBi Ground Plain Independent Antenna

380-520 MHz

- 1/2-Wave Ground Plane Independent, Wide Band Antenna
- NMO Mount, Black Chrome Finish
- Flexible Black Polymer Alloy Spring
- O-ring seals for waterproof construction
- Durable ASA base with TPU grip ring and dust seal

Electrical Specifications

Frequency Band (Tunable Range)	380-520 MHz
VSWR	<2:1, across operational bandwidth
Operational Bandwidth (min)	50 MHz
Impedance	50Ω
Gain	2 dBi
Power Rating	150 W
Polarization	Linear, Vertical
E-Plane	70 Degrees, nominal
H-Plane	Omnidirectional

Mechanical Specifications

Overall Length (max)	16 1/8 in. (409.6 mm)
Whip Material, Finish	17-7 SS, Black Chrome
Spring Material	Black Molded Polymer Alloy
Base Material	ASA w/TPU Over Mold Grip
Mounting Application	¾ inch Thru-Hole NMO Mount
NMO Cable Assembly & Connector	Sold Separately
Operating Temperature	-40° to 85° C
Corrosion	Salt Fog
Humidity	95%

Specifications subject to change without notification.

ELECTRO-MAGWAVE, INC.
2241 Pinnacle Parkway, Suite A, Twinsburg, OH 44087 t 216-453-1160 f 216-447-8828 www.emwaveinc.com