Product Data Sheet



e/m-Flex™ EMFLX-M10014-GPI

2dB Ground Plane Independent Antenna
144-174 MHz

- High Performance, Broadband Impedance Match
- Optimized VSWR for Maximum “No Ground Plane” Efficiency
- Black Chrome Finish with Flexible Polymer Alloy Spring
- O-ring Seal for IP67 Rated Waterproof Construction
- Durable ASA Base with TPU Molded Dust Seal and Grip Ring

Electrical Specifications

Frequency Band	144-174 MHz (tunable range)
Operational Bandwidth	15-20 MHz (frequency dependent)
VSWR	<1.2:1 at center frequency
	<2:1 across operational bandwidth
Impedance	50Ω
Gain	2 dBi (no ground plane installation)
Power Rating	150 W
Polarization	Linear, Vertical
E-Plane	70 Degrees, Nominal
H-Plane	Omnidirectional

Mechanical Specifications

Overall Length (max)	46 in. (1.17 m), max. @ 144 MHz
Whip Material, Finish	17-7 SS, Black Chrome
Base Material	ASA w/TPU over mold grip ring
Mounting Application	¾ inch thru-hole NMO Mount
Spring Material	Black Molded Polymer Alloy
NMO Cable Assembly & Connector	Sold separately
Operating Temperature	-40° to 85° C
Corrosion	Salt Fog
Humidity	95%

Specifications subject to change without notification.

ELECTRO-MAGWAVE, INC.
2241 Pinnacle Parkway, Suite A, Twinsburg, OH 44087 t 216-453-1160 f 216-447-8828 www.emwaveinc.com